

Ceiling mount bracket for high ceilings

Description

This ceiling mount bracket is to be used when mounting projectors to high ceilings.

Specifications

Vertical correction angle: +5°, -17°
 Horizontal slant correction angle: ±2.5°
 Horizontal turn correction angle: ±1.2°
 Dimensions (W × H × D): 344 × 340–420 × 400 mm (13-17/32 × 13-3/8–16-17/32 × 15-3/4 inches)
 Weight: 9.7 kg* (21.4 lbs)*
 Applicable projectors: PT-DZ770K/DZ770LK/DZ770S/DZ770LS/DW740S/DW740LS/DW740K/DW740LK/DW730S/DW730LS/DW730K/DW730LK/DX810S/DX810LS/DX810K/DX810LK/DX800S/DX800LS/DX800K/DX800LK/DZ680K/DZ680LK/DZ680S/DZ680LS/DW640K/DW640LK/DW640S/DW640LS/DX610K/DX610LK/DX610S/DX610LS/DZ6710/DZ6710L/DZ6700/DZ6700L/DW6300S/DW6300LS/DW6300K/DW6300LK/D6000S/D6000LS/D6000K/D6000LK/D5000S/D5000LS

* Average value. May differ depending on models.

Weights and dimensions shown are approximate. Specifications and appearance are subject to change without notice.

Parts

Attachment plate	1	Safety fitting	2
Projector mount bracket	1	Washer-fitted hexagonal bolts (M6 × 80)	2
Adjuster pole A	1	Washer-fitted screws for safety fitting (M4 × 8)	4
Adjuster pole B	1	Washer-fitted hexagonal bolts (M6 × 14)	35
Angle adjuster	1	Washer (M6)	2
Pole support bracket 1	1	Hexagonal nuts (M6)	2
Pole support bracket 2	1	Sealing packing	1
Pole fixer	1	Drop prevention kit	1

Caution:

- Mounting should be done by a qualified technician.
- Make sure that the mounting (ceiling) area has sufficient strength.
- Read the enclosed mounting instructions thoroughly before starting.
- Do not use an electric screwdriver or impact driver to tighten screws. (Use a torque driver or similar tool.)
- When the product is no longer going to be used, have it disposed of quickly by a professional disposal service.

Dimensions

Illustration shows the bracket attached to a projector.

